KAILER
HEAVY INDUSTRIES

KAILER
HEAVY INDUSTRIES

威海凯乐重工机械有限公司

KAILER
HEAVY INDUSTRIES

Tel:+8613255661443
Website:www.kailer.com
Email:228178675@qq.com
Address:No.51HaibinMiddleRoad,
Weihai,China
Tel:+8613255661443
Website:www.kailer.com
Email:228178675@qq.com
地址：山东省威海市海滨中路5-1

Whats

Weixin



KAILER
HEAVY INDUSTRIES

公司简介　Company Profile

山东凯乐重工机械制造有限公司是一家集专业研发、生产、销售 挖掘机、装载机、滑移装载机、叉车、农业挖掘机及新能源挖掘机的现代化企业，公司研发生产的挖掘机、装载机、滑移装载机、叉车、农业挖掘，规格齐全品种多，技术先进、性能优良、结构合理、操作简单、造型大方新颖、性价比高，特别适用于城乡建设、路桥管网建设、园林绿化、农田改造及中小型水利工程，是承接工程建设和农民朋友发家致富的首选。产品先后出口多个国家和地区，产品深受国内外广大用户的信赖和一致好评。
公司自成立以来认真贯彻“质量为先，诚信经营，科学管理，持续改进”的质量方针，秉承“以人为本，创建现代化企业；科技创新，打造有影响力品牌”的企业愿景，扎扎实实打基础，一心一意谋发展，为顾客提供优质的产品和服务。以质量立足市场，促进企业不断发展和壮大。
先于同行开发，优于同行性能，未来，我们将持续以“自主创新”为源动力，朝着产品高端化、运营国际化、品牌差异化方向发展，向着更高阶段、更广阔的市场进军，做装备制造领域世界价值的创造者！
我们拥有完整供应链与自营进出口权，产品稳定可靠、性价比高，远销全球多个国家与地区。提供定制化配置、整柜海运、售后支持与一站式采购方案，致力于为全球客户提供高性价比设备与省心服务。

Shandong Kaile Heavy Machinery Manufacturing Co., Ltd. is a modern enterprise specializing in the R&D, production and sales of excavators, loaders, skid steer loaders, forklifts, agricultural excavators and new energy excavators.
Our products—including excavators, loaders, skid steer loaders, forklifts and agricultural excavators—feature complete specifications, wide varieties, advanced technology, excellent performance, rational structure, simple operation, elegant and novel design, and high cost performance. They are especially suitable for urban and rural construction, road and bridge pipeline construction, landscaping, farmland renovation and small-to-medium water conservancy projects. They are the preferred choice for engineering projects and farmers to start businesses and increase income.
Our products have been exported to many countries and regions, winning the trust and high praise of users at home and abroad.
Since its establishment, the company has strictly followed the quality policy of "Quality First, Honest Operation, Scientific Management, Continuous Improvement". Upholding the corporate vision of "People-oriented, building a modern enterprise; technological innovation, creating an influential brand", we lay a solid foundation and focus on development, providing customers with high-quality products and services. We base ourselves on the market with quality and promote the continuous growth of the enterprise.
We develop ahead of peers and outperform peers in performance. In the future, we will continue to take "independent innovation" as the driving force, develop toward high-end products, international operation and brand differentiation, march into a higher stage and broader market, and become a creator of global value in the equipment manufacturing industry!
We have a complete supply chain and independent import and export rights. Our products are stable, reliable and cost-effective, and are exported to many countries and regions around the world. We provide customized configurations, full-container sea transportation, after-sales support and one-stop procurement solutions, committed to offering cost-effective equipment and worry-free service to global customers.



KAILER
HEAVY INDUSTRIES



装载机 核心用途是铲装、搬运、卸载土壤、砂石、煤炭等散状物料，可轻度铲挖、推平场地，换装属具后还能吊装、清障、除雪，是工程与料场的高频主力机。

Loaders, commonly known as forklifts, are mainly used for shoveling, handling and unloading bulk materials such as soil, sand, gravel and coal. They can perform light excavation and site leveling. With attachments, they can also lift, clear obstacles and remove snow, making them high-frequency main machinery in engineering and material yards.



装载机 核心用途是铲装、搬运、卸载土壤、砂石、煤炭等散状物料，可轻度铲挖、推平场地，换装属具后还能吊装、清障、除雪，是工程与料场的高频主力机。

Loaders, commonly known as forklifts, are mainly used for shoveling, handling and unloading bulk materials such as soil, sand, gravel and coal. They can perform light excavation and site leveling. With attachments, they can also lift, clear obstacles and remove snow, making them high-frequency main machinery in engineering and material yards.

WE CREATE CREATIVE WORK TO MAKE YOUR BUSINESS FUTURE BRIGHTER THAN BRIGHTER



我们的创造力
只为让您的工作更便捷

KAILER
HEAVY INDUSTRIES





KAILER
HEAVY INDUSTRIES

KE928





详细参数Detailed parameters

车辆尺寸 / vehicle size	5m*1.6m*2.2m	柴油发动机 / Diesel engine	新长柴 490 自吸 / New Changchai 490 Self-priming
整车重量 / Overall weight	2T	额定功率 / Rated power	42KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	1000kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	1.6m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	0.7m³
液压系统最大压力 / Maximum hydraulic system pressure	16-20Mpa	轮距 / Wheel base	2m
液压泵模式 / Hydraulic pump mode	40	轮胎型号 / Tire model	20.5-16
驱动桥型号 / Drive axle model	小轮边减速桥 / Small wheel edge reduction bridge	卸货高度 / Dumping height	2.4m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	3.1m
最小转弯半径 / minimum turning radius	3m	卸货距离 / Unloading distance	0.8m

KE932





详细参数Detailed parameters

车辆尺寸 / vehicle size	5.5m*1.8m*2.75m	柴油发动机 / Diesel engine	新长柴 490 自吸 / New Changchai 490 Self-priming
整车重量 / Overall weight	3.3T	额定功率 / Rated power	42KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	1800kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	1.9m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	0.9m³
液压系统最大压力 / Maximum hydraulic system pressure	20Mpa	轮距 / Wheel base	2.26m
液压泵模式 / Hydraulic pump mode	40	轮胎型号 / Tire model	20.5-16
驱动桥型号 / Drive axle model	轮边减速桥 / wheel edge reduction bridge	卸货高度 / Dumping height	3.2m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	3.8m
最小转弯半径 / minimum turning radius	3.2m	卸货距离 / Unloading distance	1m

KAILER
HEAVY INDUSTRIES

KE936





详细参数Detailed parameters

车辆尺寸 /vehicle size	5.5m*1.8m*2.75m	柴油发动机 / Diesel engine	新长柴 490 涡轮增压 / New Changchai 490 Turbocharged Diesel Engine
整车重量 / Overall weight	3.3T	额定功率 / Rated power	58KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	1800kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	1.9m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	0.9m³
液压系统最大压力 / Maximum hydraulic system pressure	20Mpa	轮距 / Wheel base	2.26m
液压泵模式 / Hydraulic pump mode	40	轮胎型号 / Tire model	20.5-16
驱动桥型号 / Drive axle model	轮边减速桥 / wheel edge reduction bridge	卸货高度 / Dumping height	3.2m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	3.8m
最小转弯半径 / minimum turning radius	3.2m	卸货距离 / Unloading distance	1m

KE938





详细参数Detailed parameters

车辆尺寸 /vehicle size	5.5m*1.8m*2.75m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	3.3T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	1800kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	1.9m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	0.9m³
液压系统最大压力 / Maximum hydraulic system pressure	20Mpa	轮距 / Wheel base	2.26m
液压泵模式 / Hydraulic pump mode	40	轮胎型号 / Tire model	20.5-16
驱动桥型号 / Drive axle model	轮边减速桥 / wheel edge reduction bridge	卸货高度 / Dumping height	3.2m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	3.8m
最小转弯半径 / minimum turning radius	3.2m	卸货距离 / Unloading distance	1m

KAILER
HEAVY INDUSTRIES

KE940





详细参数Detailed parameters

车辆尺寸 /vehicle size	5.9m*2m*2.85m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	4.26T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2000kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	1m³
液压系统最大压力 / Maximum hydraulic system pressure	20Mpa	轮距 / Wheel base	2.43m
液压泵模式 / Hydraulic pump mode	1045	轮胎型号 / Tire model	1670-20
驱动桥型号 / Drive axle model	中轮边减速桥 / Center wheel hub reduction axle	卸货高度 / Dumping height	3.5m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	4.2m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KE942





详细参数Detailed parameters

车辆尺寸 /vehicle size	6.16m*2m*2.85m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	5.11T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2500kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	1.2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-20
驱动桥型号 / Drive axle model	中轮边减速桥 / Center wheel hub reduction axle	卸货高度 / Dumping height	3.6m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	4.6m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KAILER
HEAVY INDUSTRIES

KE946





详细参数Detailed parameters

车辆尺寸 /vehicle size	6.35m*2m*2.85m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	5.17T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2500kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	1.2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-20
驱动桥型号 / Drive axle model	中轮边减速桥 / Center wheel hub reduction axle	卸货高度 / Dumping height	3.8m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	4.8m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KE948





详细参数Detailed parameters

车辆尺寸 /vehicle size	6.9m*2m*2.85m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	5.31T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2000kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	1.2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-20
驱动桥型号 / Drive axle model	中轮边减速桥 / Center wheel hub reduction axle	卸货高度 / Dumping height	4.2m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	5.2m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KAILER
HEAVY INDUSTRIES

KE958





详细参数Detailed parameters

车辆尺寸 /vehicle size	7m*2m*2.85m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	5.41T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2000kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	1.2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-20
驱动桥型号 / Drive axle model	中轮边减速桥 / Center wheel hub reduction axle	卸货高度 / Dumping height	4.5m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	5.5m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KE968





详细参数Detailed parameters

车辆尺寸 /vehicle size	7.2m*2m*2.85m	柴油发动机 / Diesel engine	新长柴 4102 涡轮增压 / New Changchai 4102 Turbocharged Diesel Engine
整车重量 / Overall weight	5.46T	额定功率 / Rated power	78KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2000kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2m
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	1.2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-20
驱动桥型号 / Drive axle model	中轮边减速桥 / Center wheel hub reduction axle	卸货高度 / Dumping height	4.8m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	5.8m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KAILER
HEAVY INDUSTRIES

KE958G



详细参数Detailed parameters

车辆尺寸 /vehicle size	6.35m*2m*2.85m	柴油发动机 / Diesel engine	四达 4105 涡轮增压 / Sida 4105 Supercharged
整车重量 / Overall weight	6T	额定功率 / Rated power	88KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2800kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2.4m*55cm Deep Engineering Bucket
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-24
驱动桥型号 / Drive axle model	大轮边减速桥 / Large wheel hub reduction axle	卸货高度 / Dumping height	3.8m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	4.5m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KE968G



详细参数Detailed parameters

车辆尺寸 / vehicle size	7m*2m*2.85m	柴油发动机 / Diesel engine	玉柴4105/ Yuchai 4105 Diesel Engine
整车重量 / Overall weight	6.6T	额定功率 / Rated power	85KW
冷却系统/ Cooling System	双片式液压变矩器油散热器 / Dual piece hydraulic torque converter oil radiator	额定载荷 / Rated Load	2500kg
传动系统/ Transmission system	无级变速双高低速 / Continuously variable transmission with dual high and low speeds	铲斗宽度 / Bucket width	2.4m90深粮食斗 2.4 meters 90 deep granin bucket
最大行走速度/ Maximum walking speed	35 公里 / 小时 / 35 kilometers per hour	额定铲斗容量 / Rated bucket capacity	2m³
液压系统最大压力 / Maximum hydraulic system pressure	25Mpa	轮距 / Wheel base	2.64m
液压泵模式 / Hydraulic pump mode	2080	轮胎型号 / Tire model	1670-24
驱动桥型号 / Drive axle model	大轮边减速桥 / Large wheel hub reduction axle	卸货高度 / Dumping height	3.8m
驾驶方式 / Driving method	四轮驱动 / Four-wheel drive	平举高度 / Flat lift height	4.5m
最小转弯半径 / minimum turning radius	3.3m	卸货距离 / Unloading distance	1.2m

KAILER
HEAVY INDUSTRIES

Telescopic loader

伸缩装载机





KAILER
HEAVY INDUSTRIES

KL1500





详细参数Detailed parameters

车辆尺寸 / vehicle size	5400*1800*2650	柴油发动机 / Diesel engine	云内 / YUNNEI
整车重量 / Overall weight	4300KG	额定功率 / Rated power	55KW
理论爬坡角度()/ Rated Power	15°	斗容(m)/ Bucket capacity	0.7
缩臂卸载高度(MM)/ Turning radius	2700MM	伸臂卸载高度(MM)/ Dumping height	3500MM
缩臂最大装载质量(KG) Dumping reach	1500KG	伸臂最大装载质量(KG)/ Bucketfall time	600KG
最小离地间隙(MM)/ Ground clearance	255mm	最小转弯半(mm)/ Bucket capacity	4800mm

KL1800





详细参数Detailed parameters

车辆尺寸 / vehicle size	6220*2100*2890	柴油发动机 / Diesel engine	云内 / YUNNEI
整车重量 / Overall weight	5900KG	额定功率 / Rated power	76KW
理论爬坡角度()/ Rated Power	15°	斗容(m)/ Bucket capacity	0.7
缩臂卸载高度(MM)/ Turning radius	2880MM	伸臂卸载高度(MM)/ Dumping height	3850MM
缩臂最大装载质量(KG) Dumping reach	2500KG	伸臂最大装载质量(KG)/ Bucketfall time	1000KG
最小离地间隙(MM)/ Ground clearance	255mm	最小转弯半(mm)/ Bucket capacity	4800mm

KAILER
HEAVY INDUSTRIES

KL2500



详细参数Detailed parameters

车辆尺寸 / vehicle size	6220*2100*2890	柴油发动机 / Diesel engine	云内 / YUNNEI
整车重量 / Overall weight	5900KG	额定功率 / Rated power	76KW
理论爬坡角度/ Rated Power	15°	最小转弯半(mm)/ Bucket capacity	5000mm
缩臂卸载高度(MM)/ Turning radius	2880MM	伸臂卸载高度(MM)/ Dumping height	3850MM
缩臂最大装载质量(KG) Dumping reach	2500KG	伸臂最大装载质量(KG)/ Bucketfall time	1000KG
最大崛起力(KN) The total time for a single working cyde	55	最大牵引力(KN) Weight	61

KL3000



详细参数Detailed parameters

车辆尺寸 / vehicle size	7950*2350*3000	柴油发动机 / Diesel engine	玉柴 / YUCHAI
整车重量 / Overall weight	8500KG	额定功率 / Rated power	85KW
理论爬坡角度()/ Rated Power	15°	斗容(m)/ Bucket capacity	0.7
缩臂卸载高度(MM)/ Turning radius	3600MM	伸臂卸载高度(MM)/ Dumping height	4700MM
缩臂最大装载质量(KG) Dumping reach	2500KG	伸臂最大装载质量(KG)/ Bucketfall time	1500KG
最大崛起力(KN) The total time for a single working cyde	33	最大牵引力(KN) Weight	38

KAILER
HEAVY INDUSTRIES

KL3500









详细参数Detailed parameters

车辆尺寸 / vehicle size	8200*2350*3100	柴油发动机 / Diesel engine	道依茨 / DAOYICI
整车重量 / Overall weight	9500KG	额定功率 / Rated power	92KW
理论爬坡角度/ Rated Power	35°	最小转弯半(mm)/ Bucket capacity	5850mm
缩臂卸载高度(MM)/ Turning radius	3700MM	伸臂卸载高度(MM)/ Dumping height	4800MM
缩臂最大装载质量(KG) Dumping reach	3000KG	伸臂最大装载质量(KG)/ Bucketfall time	1800KG
最大崛起力(KN) The total time for a single working cyde	33	最大牵引力(KN) Weight	38

KAILER
HEAVY INDUSTRIES

backhoe loader
反铲装载机





KAILER
HEAVY INDUSTRIES

KB15



详细参数Detailed parameters

整机操作重量 Overall Operating Weight	3200KG	车辆尺寸 / vehicle size	5.6*1.6*2.5
柴油发动机 / Diesel engine	云内/ YUNNEI	额定载重/ Rated load	1T
额定功率 / Rated power	37KW	装载斗容 / Bucket Capacity	0.5M³
转向系统/ Steering System	液压系统/ Hydraulic System	装载举升能力/ Loading Lifting Capacity	1000kg
轴距/ Wheel Base	1800mm	铲斗卸载高度/ Unloading Height of bucket	2300mm
轮距/ Wheel Tread	1200mm	铲斗卸载距离/ Dumping Distance of bucke	1325mm
档位数/ Gears	前二/后二 Two advances/two retreats	反铲斗容/ Backhoe Capacity	0.15m³
最高车速/ Max.Speed	20km	最大挖掘深度/ Max. Digging Depth	2200mm

KB25



详细参数Detailed parameters

整机操作重量 Overall Operating Weight	3800KG	车辆尺寸 / vehicle size	6.8*1.9*2.8
柴油发动机 / Diesel engine	云内/ YUNNEI	额定载重/ Rated load	1.8T
额定功率 / Rated power	42KW	装载斗容 / Bucket Capacity	0.8M³
转向系统Steering System	液压系统/ Hydraulic System	装载举升能力/ Loading Lifting Capacity	1800kg
轴距/ Wheel Base	2000mm	铲斗卸载高度/ Unloading Height of bucket	2900mm
轮距/ Wheel Tread	1500mm	铲斗卸载距离/ Dumping Distance of bucke	1325mm
档位数/ Gears	前二/后二 Two advances/two retreats	反铲斗容/ Backhoe Capacity	0.18m³
最高车速Max.Speed	28km	最大挖掘深度/ Max. Digging Depth	2500mm

KAILER
HEAVY INDUSTRIES

KB35





详细参数Detailed parameters

整机操作重量 Overall Operating Weight	8200KG	车辆尺寸 / vehicle size	6.12*2.41*3.76
柴油发动机 / Diesel engine	玉柴/ YUCHAI	额定载重/ Rated load	2.5T
额定功率 / Rated power	85KW	装载斗容 / Bucket Capacity	1M³
转向系统/ Steering System	液压系统/ Hydraulic System	装载举升能力/ Loading Lifting Capacity	2500kg
轴距/ Wheel Base	2248mm	铲斗卸载高度/ Unloading Height of bucket	2742mm
轮距/ Wheel Tread		铲斗卸载距离/ Dumping Distance of bucke	925mm
档位数/ Gears	前进4档，后退4档 Four forward, four backward	反铲斗容/ Backhoe Capacity	0.3m³
最高车速/ Max.Speed	38km	最大挖掘深度/ Max. Digging Depth	4082mm

KB45D





详细参数Detailed parameters

整机操作重量 Overall Operating Weight	7500KG	车辆尺寸 / vehicle size	7.6*2.26*2.98
柴油发动机 / Diesel engine	康明斯/ CUMMINS 93KW	额定载重/ Rated load	2.8T
额定功率 / Rated power	93KW	装载斗容 / Bucket Capacity	1.3M³
转向系统Steering System	液压系统/ Hydraulic System	装载举升能力/ Loading Lifting Capacity	2800KG
轴距/ Wheel Base	2280mm	铲斗卸载高度/ Unloading Height of bucket	2800mm
轮距/ Wheel Tread	1580mm	铲斗卸载距离/ Dumping Distance of bucke	1325mm
档位数/ Gears	前二/后二 Two advances/two retreats	反铲斗容/ Backhoe Capacity	0.3m³
最高车速Max.Speed	25km	最大挖掘深度/ Max. Digging Depth	4100/5100mm

KAILER
HEAVY INDUSTRIES

KB35





详细参数Detailed parameters

整机操作重量 Overall Operating Weight	8200KG	车辆尺寸 / vehicle size	6.12*2.41*3.76
柴油发动机 / Diesel engine	玉柴/ YUCHAI	额定载重/ Rated load	2.5T
额定功率 / Rated power	85KW	装载斗容 / Bucket Capacity	1M³
转向系统/ Steering System	液压系统/ Hydraulic System	装载举升能力/ Loading Lifting Capacity	2500kg
轴距/ Wheel Base	2248mm	铲斗卸载高度/ Unloading Height of bucket	2742mm
轮距/ Wheel Tread		铲斗卸载距离/ Dumping Distance of bucke	925mm
档位数/ Gears	前进4档，后退4档 Four forward, four backward	反铲斗容/ Backhoe Capacity	0.3m³
最高车速/ Max.Speed	38km	最大挖掘深度/ Max. Digging Depth	4082mm

KB45D





详细参数Detailed parameters

整机操作重量 Overall Operating Weight	7500KG	车辆尺寸 / vehicle size	7.6*2.26*2.98
柴油发动机 / Diesel engine	康明斯/ CUMMINS 93KW	额定载重/ Rated load	2.8T
额定功率 / Rated power	93KW	装载斗容 / Bucket Capacity	1.3M³
转向系统Steering System	液压系统/ Hydraulic System	装载举升能力/ Loading Lifting Capacity	2800KG
轴距/ Wheel Base	2280mm	铲斗卸载高度/ Unloading Height of bucket	2800mm
轮距/ Wheel Tread	1580mm	铲斗卸载距离/ Dumping Distance of bucke	1325mm
档位数/ Gears	前二/后二 Two advances/two retreats	反铲斗容/ Backhoe Capacity	0.3m³
最高车速Max.Speed	25km	最大挖掘深度/ Max. Digging Depth	4100/5100mm


Thank you.!
We hope you will become our partner.